

RECEIVED
CENTRAL FAX CENTER

Serial No.: 10/588,022

PU040041 DEC 19 2008

Listing and Amendments to the Claims

Please **rewrite** claims 9 and 12 as indicated. Please **cancel** claim 10.

1. (Previously Presented) A projection lens family comprising a plurality of lens systems, each having a double-gauss base architecture with aspheric lens elements at the beginning and end of the lens system with a system stop therebetween and an acromatic lens element pair between each aspheric lens and the system stop,

wherein at least one of the lens systems is optimized with one or more lens elements added to the base architecture between the aspheric lens elements at the beginning and end of the lens system.

2. (Original) A projection lens family according to claim 1 wherein the lenses vary in length within the projection lens family.

3. (Original) A projection lens family according to claim 2 wherein at least one of the lens systems is optimized for a system length of less than 1050 millimeters.

4-5. (Cancelled).

6. (Original) A projection lens family according to claim 1 wherein the lens systems are optimized to provide maximum distortions varying from about 0.55% to about 0.30% and a Modulus Transfer Functions varying from about 0.48 to about 0.69.

7. (Original) A projection lens family according to claim 6 wherein the lens systems use from 6 to 9 lens elements.

Serial No.: 10/588,022

PU040041

8. (Original) A projection lens family according to claim 1 wherein the acromatic lens element pairs for at least one lens system are formed from a combination of inexpensive glass materials chosen from the group consisting of: SF14, SF15, BAK1, and BALF4.

9. (Currently Amended) A projection lens system comprising a double-gauss architecture with aspheric lens elements at the beginning and end of the lens system with a system stop therebetween and an acromatic lens element pair between each aspheric lens and the system stop,

wherein the acromatic lens element pairs for at least one lens system are formed from a combination of inexpensive glass materials chosen from the group consisting of: SF14, SF15, BAK1, and BALF4; and

wherein the lens systems is configured to provide maximum distortion of less than about 0.55% and a Modulus Transfer Functions of at least about 0.48.

10-11. (Cancelled).

12. (Currently Amended) A projection lens system according to claim ~~10~~ 9 wherein the lens system has at least six lens elements and no more than nine lens elements.

13. (Original) A projection lens system according to claim 9 further comprising an additional aspheric lens disposed between the aspheric lens at the beginning of the lens system and the acromatic lens between the aspheric lens at the beginning of the lens system and the system stop.

Serial No.: 10/588,022

PU040041

14. (Original) A projection lens system according to claim 9 further comprising an additional acromatic lens element pair disposed between the aspheric lens at the beginning of the lens system and the acromatic lens between the aspheric lens at the beginning of the lens system and the system stop.

15. (Original) A projection lens system according to claim 14 further comprising an additional aspheric lens disposed between the aspheric lens at the end of the lens system and the system stop and an additional acromatic lens disposed between the aspheric lens at the beginning of the lens system and the system stop.

16. (Original) A projection lens system according to claim 9 wherein the lens system is optimized for lenses that provide a system length of less than 1050 millimeters.